



4226T

TELESCOPIC WHEEL LOADER

Control. Power. Strength.

With a 2.6 tonne tipping load and 4.2m lift height, the Yardex 4226T is powered by a Euro 5 Perkins turbo diesel engine with Danfoss hydrostatic drive and PWG Italian hydraulics. Premium controls, oil immersed disc brakes and a comfortable ergonomic cab deliver reliable performance, backed by our UK & Irish parts & support network.

KEY FEATURES

- 2600kg rated lift capacity
- 4220mm maximum lift height
- Perkins 404J-E22T Stage V engine (61.2HP / 45kW)
- 4300kg operating weight
- Hydrostatic transmission (HST with 2 axles)
- 32 km/h top speed
- Danfoss drive motor with differential lock
- PWG hydraulic pump with European system
- Electric proportional joystick with inching function
- Electric floating function
- Articulated pendulum joint for stability
- Wet brake axle
- Overload alarm system
- Bluetooth key with push start
- High-performance hydraulic system
- Durable drivetrain
- Operator-focused design



**2600KG
LOAD
CAPACITY**



**3 YEAR
WARRANTY
2000 HOURS
STANDARD**



**SUPPORTED BY
FULL UK &
IRELAND
PARTS STOCK**

PERFORMANCE	Rated Load (kg)	2600
	Bucket Capacity (m ³)	0.67
	Net Weight (kg)	4300
	Max Lifting Height (mm)	4220
	Max Driving Speed (km/h)	32
	Max Turning Angle (deg)	45°
DIMENSIONS	Overall Length (mm)	4755
	Overall Width (mm)	1520
	Overall Height (mm)	2434
	Wheelbase (mm)	2140
	Min Turning Radius (mm)	3618
ENGINE	Manufacturer	Perkins
	Model	404J-E22T
	Power (Kw / HP)	45 / 61.2
	Displacement (cc)	2200
	Cooling	Water Cooling
	Cylinders	4
	Rated Speed (rpm)	2800
HYDRAULICS	Drive Pump Pressure (bar)	350
	Working Pump Flow (L/min)	52
	Working Pump Pressure (bar)	215 bar
DRIVETRAIN	Transmission	HST + 2 Axles
	Gear Shift	Electric
	Steering Type	Articulated
	Steering Cylinders	2
	Service Brake	Wet Brake
	Parking Brake	Electric Parking Brake
	Tyre Size	15.0/55-17