



T4515

TELESCOPIC HANDLER

Manoeuvrable. Reliable. Versatile.

The T4515 telehandler is a compact, reliable machine built for demanding environments, combining a powerful turbocharged Yanmar engine with smooth, precise operation thanks to its familiar Italian PWG hydraulics.

Engineered for use across diverse applications and industries, the T4515 offers excellent control, versatility and manoeuvrability. An ideal machine for a wide range of jobs around yards and rough terrain, backed by our UK & Irish parts & support network.

KEY FEATURES

- 1.5 ton lift capacity
- 43.4hp (32.4kw) Yanmar 3 cylinder Euro 5 turbocharged engine
- Hydrostatic 8/20kph two speed transmission
- Italian PWG hydraulics
- Three steering modes - 2/4 wheel steer + crab
- Euro headstock
- Max lift height: 4537mm
- Max reach: 2290mm
- Operating weight: 2750kg
- Dimensions: L: 3.95m W: 1.56m H: 2m



**1500KG LIFT
CAPACITY**
REACH 2290MM



**3 YEAR
WARRANTY**
2000 HOURS
STANDARD



**SUPPORTED BY
FULL UK &
IRELAND
PARTS STOCK**

PERFORMANCE	Max. payload (kg)	1500
	Bucket capacity (m3)	0.45
	Operating weight (kg)	2750
DRIVETRAIN	Tyres	10.0/75-15.3 or 29 x 12.5-15
	Steering modes	All-wheel / front-wheel / crab steering
FEATURES	Lockable cabin, tank and bonnet	Yes
	Hydraulic quick-hitch system	Optional with Euro attachment
	Third hydraulic oil circuit for attachments	Yes
DIMENSIONS	Total length with standard bucket (mm)	3945
	Total length with pallet fork (mm)	4080
	Total length without attachment (mm)	2980
	Axle centre to bucket pin (mm)	450
	Wheelbase (mm)	1930
	Rear overhang (mm)	430
	Height above cabin (mm)	1995
	Total working height with bucket (mm)	5280
	Total working height with pallet fork (mm)	4980
	Maximum height of bucket pivot point (mm)	4537
	Overloading height of bucket - telescope extended (mm)	4165
	Overloading height of pallet fork - telescope extended (mm)	4300
	Overloading height of bucket - telescope retracted (mm)	2950
	Overloading height of pallet fork - telescope retracted (mm)	3080
	Maximum dumping height - telescope extended (mm)	3570
	Maximum dumping height - telescope retracted (mm)	2355
	Maximum reach with bucket - telescope retracted (mm)	475
	Maximum reach with pallet fork - telescope extended (mm)	2290
	Maximum reach with pallet fork - telescope retracted (mm)	930
	Total height (mm)	1564
	Track width (mm)	1245
	Ground clearance (mm)	295
	Maximum radius with bucket (mm)	3550
	Maximum radius with pallet fork (mm)	3420
	Radius at outer edge (mm)	2695
	Inner radius (mm)	950
	Roll-back angle with telescopic retracted (deg)	52
	Dumping angle with telescopic retracted (deg)	31
	Roll-back angle at ground level (deg)	44